



State Water Authority
Certificate of Approval for Water Supply Product

The State Water Authority of Sarawak hereby gives approval for this water supply product to be used in the Water Supply Authority areas within Sarawak, under the powers vested in Part III Regulation 9 of the Water Supply Regulations 1995:

Name of Water Supply Product: SERVICING VALVE (COPPER ALLOY) FOR WATER SERVICE	Name & Address of Certificate Holder: WELL-BUILT ALLOY INDUSTRIES SDN BHD NO 5 JALAN RIANG 24 TAMAN GEMBIRA 81200 JOHOR BAHRU, JOHOR
Type: Fitting	Nature of Business Entity of Certificate: Manufacturer
Brand: CITY	Name & Address of Manufacturer: WELL-BUILT ALLOY INDUSTRIES SDN BHD NO 5 JALAN RIANG 24 TAMAN GEMBIRA 81200, JOHOR BAHRU, JOHOR
Standard: BS 6675:1986	
Class & Size: See schedule on the reverse page	
Validity Period: <u>21/11/2025</u> to <u>18/11/2026</u>	Name & Address of Principal: WELL-BUILT ALLOY INDUSTRIES SDN BHD NO 5 JALAN RIANG 24 TAMAN GEMBIRA 81200, JOHOR BAHRU, JOHOR
Date of Issue: 21/11/2025	
Product Category: Category A	

This approval is given subject to the following:

- i. The State Water Authority of Sarawak reverses the right to withdraw this approval at anytime and shall not be obliged to give any reason whatsoever.
- ii. The specifications for the water supply products shall not differ from that originally submitted in the application for approval.
- iii. There should not be any unsuitability in the use of this product.
- iv. This certificate of approval shall not be used for any advertisement purpose. However, a copy can be used as evidence of approval only.
- v. This certificate of approval shall become invalid upon expiry of SPAN Product Certificate Registration or SIRIM Licence or IKRAM Bhd Certification or other internationally recognized certification of the product, whichever is earlier.



Schedule

COMPANY NAME: WELL-BUILT ALLOY INDUSTRIES SDN BHD

PRODUCT: SERVICING VALVE (COPPER ALLOY) FOR WATER SERVICE

VALIDITY PERIOD: 21/11/2025 - 18/11/2026

CERTIFICATE NUMBER: SWA/F/1147

Model	Series	Description
LOCKABLE VALVE (P); PATTERN : SPHERICAL PLUG	MAXIMUM WORKING PRESSURE : 16 BAR; MAXIMUM WORKING TEMPERATURE : 30°C	BODY MATERIAL : CW617N; END CONNECTION : SCREW ENDS / NOMINAL SIZE : 3/4" / LOCKABLE VALVE (P)
LOCKABLE VALVE (J AND J1); PATTERN : SPHERICAL PLUG	MAXIMUM WORKING PRESSURE : 16 BAR; MAXIMUM WORKING TEMPERATURE : 30°C	BODY MATERIAL : CW617N; END CONNECTION : SCREW ENDS / NOMINAL SIZE : 3/4" / LOCKABLE VALVE (J AND J1)
LOCKABLE VALVE (K); PATTERN : SPHERICAL PLUG	MAXIMUM WORKING PRESSURE : 16 BAR; MAXIMUM WORKING TEMPERATURE : 30°C	BODY MATERIAL : CW617N; END CONNECTION : SCREW ENDS / NOMINAL SIZE : 3/4" / LOCKABLE VALVE (K)

Model	Series	Description
LOCKABLE VALVE; PATTERN: SPHERICAL PLUG	MAXIMUM WORKING PRESSURE: 16BAR; MAXIMUM WORKING TEMPERATURE: 30°C	BODY MATERIAL: CW617N; END CONNECTION: SCREW ENDS / NOMINAL SIZE: 1/2" & 3/4" / LOCKABLE VALVE

End of Page
